

TMP GEOSYNTHETICS – HDPE Geocell GC0740

Introduction

- TMP Geocell is engineered for soil stabilization applications, it is used to help improve the performance of standard construction materials and erosion-control treatments.
- TMP Geocell is a lightweight and flexible three-dimensional, expandable panels made from high-density polyethylene(HDPE) strips which are ultrasonically bonded together to form an extremely strong configuration. TMP Geocell System can be filled with a wide range of material: aggregate, concrete, sand, soil, etc.

Applications

- Erosion Control
- Slope Protection
- Retaining Wall
- Slope Protection Applications
- Load Support
- Channel Protection
- Ground Stabilization

Specifications

Index Properties	Test Method	Units	Values
■ Polymer	–	–	HDPE
■ Carbon Black content	ASTM D 1603	%	≥1.5
■ Density	ASTM D 1505	g/cm ³	≥0.94
■ Sheet Thickness	ASTM D 5199	mm	1.10
■ Seam Peel Strength	–	N	1060
■ Weld Spacing	–	mm	400
■ Cell Depth	–	mm	75

Dimensions

■ Expanded Cell Size (width×length)	–	mm	295 X 250
■ Expanded Panel Size (width×length)	–	m	4 X 5
■ Expanded Panel Area	–	m ²	20 ±1%

TMP Laboratory is improving continuously with the purpose of assuring reliable quality. TMP Geosynthetics reserves the right to change the product specifications at any time.



TMP GEOSYNTHETICS – HDPE Geocell GC1040

Introduction

- TMP Geocell is engineered for soil stabilization applications, it is used to help improve the performance of standard construction materials and erosion-control treatments.
- TMP Geocell is a lightweight and flexible three-dimensional, expandable panels made from high-density polyethylene(HDPE) strips which are ultrasonically bonded together to form an extremely strong configuration. TMP Geocell System can be filled with a wide range of material: aggregate, concrete, sand, soil, etc.

Applications

- Erosion Control
- Slope Protection
- Retaining Wall
- Slope Protection Applications
- Load Support
- Channel Protection
- Ground Stabilization

Specifications

Index Properties	Test Method	Units	Values
■ Polymer	–	–	HDPE
■ Carbon Black content	ASTM D 1603	%	≥1.5
■ Density	ASTM D 1505	g/cm ³	≥0.94
■ Sheet Thickness	ASTM D 5199	mm	1.10
■ Seam Peel Strength	–	N	1420
■ Weld Spacing	–	mm	400
■ Cell Depth	–	mm	100

Dimensions

■ Expanded Cell Size (width×length)	–	mm	295 X 250
■ Expanded Panel Size (width×length)	–	m	4 X 5
■ Expanded Panel Area	–	m ²	20 ±1%

TMP Laboratory is improving continuously with the purpose of assuring reliable quality. TMP Geosynthetics reserves the right to change the product specifications at any time.



TMP GEOSYNTHETICS – HDPE Geocell GC1540

Introduction

- TMP Geocell is engineered for soil stabilization applications, it is used to help improve the performance of standard construction materials and erosion-control treatments.
- TMP Geocell is a lightweight and flexible three-dimensional, expandable panels made from high-density polyethylene(HDPE) strips which are ultrasonically bonded together to form an extremely strong configuration. TMP Geocell System can be filled with a wide range of material: aggregate, concrete, sand, soil, etc.

Applications

- Erosion Control
- Slope Protection
- Retaining Wall
- Slope Protection Applications
- Load Support
- Channel Protection
- Ground Stabilization

Specifications

Index Properties	Test Method	Units	Values
■ Polymer	–	–	HDPE
■ Carbon Black content	ASTM D 1603	%	≥1.5
■ Density	ASTM D 1505	g/cm ³	≥0.94
■ Sheet Thickness	ASTM D 5199	mm	1.10
■ Seam Peel Strength	–	N	2130
■ Weld Spacing	–	mm	400
■ Cell Depth	–	mm	150

Dimensions

■ Expanded Cell Size (width×length)	–	mm	295 X 250
■ Expanded Panel Size (width×length)	–	m	4 X 5
■ Expanded Panel Area	–	m ²	20 ±1%

TMP Laboratory is improving continuously with the purpose of assuring reliable quality. TMP Geosynthetics reserves the right to change the product specifications at any time.



TMP GEOSYNTHETICS – HDPE Geocell GC2040

Introduction

- TMP Geocell is engineered for soil stabilization applications, it is used to help improve the performance of standard construction materials and erosion-control treatments.
- TMP Geocell is a lightweight and flexible three-dimensional, expandable panels made from high-density polyethylene(HDPE) strips which are ultrasonically bonded together to form an extremely strong configuration. TMP Geocell System can be filled with a wide range of material: aggregate, concrete, sand, soil, etc.

Applications

- Erosion Control
- Slope Protection
- Retaining Wall
- Slope Protection Applications
- Load Support
- Channel Protection
- Ground Stabilization

Specifications

Index Properties	Test Method	Units	Values
■ Polymer	–	–	HDPE
■ Carbon Black content	ASTM D 1603	%	≥1.5
■ Density	ASTM D 1505	g/cm ³	≥0.94
■ Sheet Thickness	ASTM D 5199	mm	1.10
■ Seam Peel Strength	–	N	2840
■ Weld Spacing	–	mm	400
■ Cell Depth	–	mm	200

Dimensions

■ Expanded Cell Size (width×length)	–	mm	295 X 250
■ Expanded Panel Size (width×length)	–	m	4 X 5
■ Expanded Panel Area	–	m ²	20 ±1%

TMP Laboratory is improving continuously with the purpose of assuring reliable quality. TMP Geosynthetics reserves the right to change the product specifications at any time.

